	(SAMPLE)		(SAMPLE)	D-4	(SAMPLE)
Ву:		_lts:		Date:	

FOR PURPOSES OF THIS WARRANTY, MULE-HIDE WILL BE DEEMED THE PREVAILING PARTY IF THE OWNER RECOVERS NOTHING OR A

SUM LESS THAN WAS OFFERED IN SETTLEMENT. MULE-HIDE PRODUCTS CO., INC.

Mule-Hide Owners Care and Maintenance Information

Thank you for choosing a Mule-Hide Roofing System! Following are some recommendations on how to care for your roof to help ensure a long useful service life.

Your roofing system should be inspected at least twice a year, and after every major storm. These inspections should be performed by a Mule-Hide Warranty Eligible Applicator or by someone specially trained in single-ply roofing installations. Maintain a log of maintenance procedures and people accessing the roof.

Keep the roof surface clean of debris, especially at drain areas to avoid clogging. Good roofing practice suggests that water not be allowed to remain on the roof for more than 48 hours after a rain. Keeping the roof clear of debris will allow for proper water run-off and avoid overloading the roof with standing water.

Keep chemical and petroleum products (acids, chemicals, solvents, greases, oils, or any liquids containing petroleum products) off the membrane to avoid degradation. If swelling occurs, contact Mule-Hide immediately.

Do not exhaust kitchen wastes (vegetable oils) or other animal fats directly onto the roof surface of EPDM or SA Modified Bitumen membranes. If incidental contact is likely, contact Mule-Hide for recommendations on preventative measures.

TPO and PVC membranes may be used for restaurant roofs but must have a rooftop maintenance program in-place to ensure that accumulations of animal fats/grease are regularly removed and the membrane surface is cleaned periodically. See Mule-Hide's Care and Maintenance Overview for specific cleaning instructions.

Walkways must be provided if regular rooftop traffic is required, such as servicing of rooftop equipment. Exercise caution when not walking on walkways, especially on white membranes (White-on-Black EPDM, Elastomeric Acrylic Coatings, TPO and PVC) since ice or frost build-up may not be visible. All membranes are slippery when wet.

When it is necessary for workers to be on the roof to service rooftop equipment, e.g., HVAC units, antennas, etc., workers should be cautioned to use walkways and to exercise care with their tools and equipment to avoid puncturing the roofing membrane. Mule-Hide recommends that the building owner or property manager keep a "Roof-top Maintenance and Activity Log" to track dates and activities by personnel or other trades.

Handprints, footprints, general traffic grime, industrial pollutants and environmental dirt may be cleaned from the surface of the membrane by scrubbing with detergent and water, then rinsing with clean water. To maximize and maintain reflectivity, white membrane(s) should be cleaned once every two years.

Keep roof maintenance items, such as counterflashings, metal curbs, metal ducts, etc. sealed watertight at all times.

If any changes are to be made to the roofing system (HVAC equipment, TV antennas, tie-ins to new roofing systems, etc), contact Mule-Hide for prior approval.

If you have a leak, check for the obvious such as clogged roof drains, broken skylights, loose counterflashings, broken water pipes, leaking roof units, and storm damage. Note when the leaking occurs. Items such as heavy or light rain, wind direction, temperature and time of day are important clues for tracking suspected leaks. Does the leak start and stop with the rain, or does leaking continue after the rain has ceased?

If you believe that the leak is covered under the Mule-Hide warranty, please notify Mule-Hide's Warranty Department at (800) 786-1492 as soon as possible, and follow up with written notification. Leaks resulting from the deterioration or failure of building components or physical damage are not covered by the Warranty. The building owner must pay the investigation and repair cost if the problem is found to be outside the scope of the Warranty.

For temporary repairs in the Mule-Hide membrane, use a one-part urethane sealant and contact Mule-Hide.

Do not use Any Asphalt Product to make repairs as it **WILL** degrade the membrane. If any asphalt product is used on the roofing membrane, that area will have to be removed and replaced at the Owner's expense.

The preceding Recommended Care and Maintenance for Mule-Hide Roofs information is not meant to be exhaustive and is for illustrative purposes only. Please refer to Mule-Hide's Care and Maintenance Overview literature for more information. Compliance with the above items will aid in assuring a durable, watertight membrane roofing System.

Mule-Hide Products Co., Inc.

P.O. Box 1057 Beloit, WI 53512-1057 Phone: 800-786-1492 Fax: 888-218-7838 www.mulehide.com